

These disposable transmitters are available with either pulsed or continuous signals. They produce a comparable signal range to the standard line of Comtel transmitters, with extended operating hours.

### Features:

- Lower cost, disposable transmitter.
- Factory set to Pulsed or Continuous
- Magnet used for activation / deactivation
- Custom sizes available for your pig or tool



### Common Specifications:

- Lightweight, tough construction
- Non-replaceable lithium battery
- Temperature: -76 to +185°F (-60 to +85°C)

**Can be activated and deactivated multiple times within battery life.**

Simply place magnetic cap on the specified end of the transmitter to deactivate it, saving battery life.

Model	Dimensions (O.D. x Length)	Range* (ft)	Std. Hours** (Pulse/Cont.)	Pressure (psi)
DT-CR123	1.00" x 4.25"	> 30	144 / 74	2,000
DT-2AA	1.25" x 6.0"	> 45	185 / 57	2,000
DT-4C-L	1.75" x 9.5"	> 50	500 / 130	2,000
DT-4C-H	1.75" x 9.5"	> 60	265 / 90	2,000
DT-4D-L	2.48" x 11.2"	> 80	382 / 111	2,000
DT-4D-H	2.48" x 11.2"	> 90	185 / 57	2,000

\* Tested range is determined in open air, utilizing a Comtel receiver. Built range/hours can vary ± 5%.

\*\* Specify either Pulsed or Continuous signal when ordering (transmitter is not switchable).



[www.bestpigtracker.com](http://www.bestpigtracker.com)