

Transmitters

These durable transmitters are available in both standard and coded frequencies. There are many standard types, but they can be custom made to meet specific job requirements.



Features:

- **New TX-HP** models (Now in all sizes) have up to 30% more range with the same size and battery life.
- **Switches** allow one transmitter to do the work of two!
 - ◊ Switch between Pulsed and Continuous or between two different codes.
- **Custom sizes** to fit your pig or tool.
- **We can also match other manufacturers' transmitter sizes** on request.



Common Specifications:

- **Standard Batteries:** Alkaline (Lithium in some models or on request – contact us)
- **Temperature:**
 - ◊ Alkaline: -4 to +130°F (-20 to +54°C)
 - ◊ Lithium: -76 to +185°F (-60 to +85°C)
 - ◊ More Extreme Temperatures on Request
- **Warranty:** 1 Year

See back for model specific specs.



www.bestpigtracker.com

Detailed Standard Specifications: (Custom Transmitters Available on Request)

Switches: Switch inside used for either Pulsed/Cont. or two different codes (specify when ordering).

Std. Hours: Specify desired battery life when ordering. Hours listed are standard. All runtimes are adjustable with longer hours and less range. Factory set.

Std. Range: Tested range is determined in open air, utilizing a Comtel Systems Ltd. receiver. Range and hours can vary $\pm 5\%$ depending on build.

| Model | Battery | Dimensions (O.D. x Length) | Std. Range (ft) (Est. Open Air) | Std. Hours (Pulse / Cont.) |
|--------------|-----------------------|-------------------------------|------------------------------------|-------------------------------|
| TX-HP-Bullet | 1 x AA Lithium (Saft) | 1.00" x 4.25" | 25+ | 100 / 50 |
| TX-HP-1AAA | 1 x AAA Alkaline | 0.875" x 2.50" | 20+ | 70 / 30 |
| TX-HP-2AAA | 2 x AAA Alkaline | 0.875" x 4.35" | 24+ | 80 / 30 |
| TX-HP-3AAA | 3 x AAA Alkaline | 0.875" x 6.30" | 35+ | 140 / 50 |
| TX-HP-1/2AA | 1 x 1/2AA Lithium | 1.25" x 1.95" | 20+ | 50 / 20 |
| TX-HP-VTOOL | 1 x AA Lithium (Saft) | 0.985" x 4.175" | 25+ | 100 / 50 |
| TX-HP-2CR123 | 2 x CR123 | 1.37" x 3.00" | 30+ | 40 / 20 |
| TX-HP-1AA | 1 x AA Alkaline | 1.25" x 2.95" | 25+ | 120 / 35 |
| TX-HP-2AA | 2 x AA Alkaline | 1.30" x 5.15" | 40+ | 130 / 50 |
| TX-HP-3AA | 3 x AA Alkaline | 1.25" x 7.00" | 45+ | 120 / 40 |
| TX-HP-2C | 2 x C Alkaline | 1.64" x 5.10" | 45+ | 180 / 60 |
| TX-HP-3C | 3 x C Alkaline | 1.64" x 7.72" | 55+ | 250 / 70 |
| TX-HP-4C | 4 x C Alkaline | 1.64" x 8.90" | 65+ | 250 / 65 |
| TX-HP-2D | 2 x D Alkaline | 2.48" x 6.45" | 65+ | 300 / 90 |
| TX-HP-4D | 4 x D Alkaline | 2.48" x 11.20" | 90+ | 490 / 120 |
| TX-HP-6D | 6 x D Alkaline | 2.48" x 16.25" | 90+ | 650 / 200 |
| TX-HP-8D | 8 x D Alkaline | 2.48" x 22.35" | 100+ | 1300 / 500 |