

# Transmitters

These durable transmitters are available in both standard and coded frequencies. There are many standard types, but they can be custom made to meet specific job requirements.



## Features:

- **New TX-HP** models (C and D cell sizes) have up to 30% more range with the same size and battery life.
- **Switches** allow one transmitter to do the work of two!
  - ◊ Switch between Pulsed and Continuous or between two different codes.
- **Custom sizes** to fit your pig or tool.
- **We can also match other manufacturers' transmitter sizes** on request.

## Common Specifications:

- **Standard Batteries:** Alkaline (Lithium in some models or on request – contact us)
- **Temperature:**
  - ◊ Alkaline: -4 to +130°F (-20 to +54°C)
  - ◊ Lithium: -76 to +185°F (-60 to +85°C)
  - ◊ More Extreme Temperatures on Request
- **Warranty:** 1 Year



**See back for model specific specs.**



[www.bestpigtracker.com](http://www.bestpigtracker.com)

## Detailed Standard Specifications: (Custom Transmitters Available on Request)

### Switches Legend:

0. Manufactured permanently as Pulsed, Continuous, or Coded (specify when ordering).
1. Switch inside used for either Pulsed/Cont. or two different codes (specify when ordering).

**Std. Hours:** Specify desired battery life when ordering. Hours listed are standard. All runtimes are adjustable with longer hours and less range. Factory set.

Model	Battery	Dimensions (O.D. x Length)	Switches (see above)	Std. Hours (Pulse / Cont.)
TX-CR123 (Bullet)	1 x CR123	1.00" x 4.25"	1	100 / 40
TX-1AAA	1 x AAA Alk.	0.875" x 2.50"	0	40 / 15
TX-2AAA	2 x AAA Alk.	1.05" x 4.42"	1	75 / 25
TX-3AAA	3 x AAA Alk.	1.05" x 6.02"	1	90 / 30
TX-1/2AA	1 x 1/2AA Lithium	0.985" x 1.95"	0	40 / 15
TX-VTOOL	Either AAA, 1/2 AA, AA, or CR123 (Lith. or Alk.)	0.985" x 4.175"	1	100 / 40 (with CR123)
TX-2CR123	2 x CR123	1.37" x 3.00"	1	50 / 15
TX-1AA	1 x AA Alk.	1.05" x 2.95"	1	100 / 30
TX-2AA	2 x AA Alk.	1.30" x 5.15"	1	120 / 40
TX-3AA	3 x AA Alk.	1.25" x 7.00"	1	140 / 35
TX-HP-2C	2 x C Alk.	1.64" x 5.10"	1	250 / 65
TX-HP-3C	3 x C Alk.	1.64" x 7.72"	1	270 / 90
TX-HP-4C	4 x C Alk.	1.64" x 8.90"	1	250 / 70
TX-HP-2D	2 x D Alk.	2.48" x 6.45"	1	480 / 130
TX-HP-4D	4 x D Alk.	2.48" x 11.20"	1	500 / 145
TX-HP-6D	6 x D Alk.	2.48" x 16.25"	1	1000 / 350
TX-HP-8D	8 x D Alk.	2.48" x 22.35"	1	1500 / 500